

GFITool TUBE FACING MACHINES

SMALL TUBE – THIN WALL FACING MACHINES



The GF-1.0, GF-1.5, GF-2.0 & GF-2.5 tube facing tools are available as either a portable battery-operated unit (240v charger) or as plug-in to standard 110v or 240v mains power. Bosch 18V Lion or Metabo 110/220V professional power supply.



Graduated micro-feed advancement for controlled material removal. Standard stainless steel collet sizes available. Optional bevelling tool holder provide various bevelling angle.



These tube facing tools will give your tube applications a quick and clean prep to ensure a clean and flat surface to weld on.



All GF Tube Facing Machines come in a flight case and with a tool bag containing the necessary screwdrivers and allen keys to change the facing tool bit and clamps.



GFITool TUBE FACING MACHINES



The larger GF series tube facing machines are capable of clamping tube diameters from (GF-3 model) 12.7mm (1/2") to 76.2mm (3") and (GF-4.5 model) from 12.7mm (1/2") to 114.3 mm (4.5"), while facing up to a maximum wall thicknesses of Sch. 80 4" Stainless Steel.



Please Note: Model GF-3.0 and GF-4.5 are only available for AC 220V / 1.3KW mains as power supply.

SPECIFICATIONS

Model	Working Range	Weight	Motor Type
GF-1.0	3~25.4mm (1/8"-1")	2.0 kg	Metabo1.3kw 220v/500hz or Bosch Battery:14v
GF-1.5	3~38.1mm (1/8"-1.5")	2.5 kg	Metabo1.3kw 220v/500hz or Bosch Battery:18v
GF-2.0	6-50.8mm (1/4"-2")	2.8 kg	Metabo1.3kw 220v/500hz or Bosch Battery:18v
GF-2.5	9~63.5mm (3/8"-2.5")	3.5 kg	Metabo1.3kw 220v/500hz or Bosch Battery:18v
GF-3.0	12.7~76.2mm(1/2"-3")	9.5kg	Metabo 1.3kw/220v/50hz
GF-4.5	12.7~114.3mm (1/2"-4.5")	16.5 kg	Metabo 1.3kw220v/50hz